

# TANDEM PULLEY

Double pulley for Tyrolean traverses and zip-lines on both textile ropes and steel cables. Two stainless steel sheaves are mounted on a pair of sealed ball bearings.

## DESCRIPTION

Two stainless steel sheaves for both textile ropes and steel wire cables. Maximum diameter of textile rope 13 mm and maximum diameter of wire cable 12mm

Each sheave is equipped with a pair of sealed ball bearings for great durability

Hard aluminum alloy body is black anodized and protects the sheaves from damage

Large attachment point can accommodate up to three carabiners

Second attachment point for back-up carabiner or tackle systems building



## KEY FEATURES

- stainless steel sheaves
- excellent durability
- versatility

## STANDARDS

CE 1019  
EN 12278

## FEATURES

25 kN	max $\varnothing$ 12 mm	max $\varnothing$ 13 mm	290 g / 10,2 oz	unique number	warranty

## MATERIAL COMPOSITION

- 40% aluminum alloy
- 60% stainless steel

## TECHNICAL DATA

## MAINTENANCE

Without taking wear or mechanical damage into account Tandem pulleys may be used 15 years since the date of production and 10 years since the date of first use. Depending on the condition of the product and its history it may be necessary to retire it immediately.

Mobile components may be lubricated with a specific silicone based lubricant.

beware of salt	washing	drying	silicon oil	read instructions