BODY II
energy speed

Fully adjustable fall-arrest harness with various attachment points, speed buckles and comfortable padding. Suitable for working situations with maximum freedom of movement during work positioning.

DESCRIPTION

Removable and washable shoulder and leg loops padding provides great comfort.

Webbing stitched in the buckles simplifies handling.

Front attachment point for fall arrest according to EN 361 marked with additional „A" marking.

Speed buckles enable fluent and fast adjustment to fit the user's body.

Two gear loops with max. load 15 kg.

Shoulder and leg loop padding with reflective straps provide higher visibility in dark conditions.

Loops for HOOK SLOT.

Rear attachment point according to EN 361 marked with „A" label.

Mesh net triangle for higher ventilation.

Waist belt allows horizontal or vertical movement.

Side attachment points for work positioning according to EN 358.

4 additional plastic hooks for light gear attachment.

KEY FEATURES

- removable and washable shoulder and leg loops padding
- stitched waist belt padding allows horizontal or vertical movement of the padding

STANDARDS

CE 1019

EN 361:02

EN 358:99

FEATURES

XL/XXL
2 450 g / 78.8 oz

№
unique number

3 YEARS
warranty

MATERIALS

- **40 %** PES
- **27 %** EVA foam
- **10 %** PAD
- **9 %** steel
- **6 %** light alloy
- **5 %** PE
- **3 %** synthetic rubber

TECHNICAL DATA



	S/M/L	XL/XXL	XXXL
A [cm]	75–125	85–135	100–160
A [in]	29.5–49	33–53	39–63
B [cm]	55–70	65–90	65–105
B [in]	21.6–27.5	25.6–35.5	25.6–41
C [cm]	150–185	180–210	180–210
C [ft]	4.9–6	5.9–6.9	5.9–6.9
m [g]	2 250	2 450	2 600

singing rock®

info@singingrock.cz
www.singingrock.com

COMPARISON

BODY ENERGY SPEED VS. BODY SPEED

- better comfort due to padded waist belt, shoulders and leg loops
- stitched waist belt for work positioning according to EN 358
- reflective straps on shoulder and leg loops padding for higher visibility
- 2 gear loops and 4 plastic D-rings for gear attachment

BODY SPEED

MAINTENANCE

Lifetime of this product depends on the frequency and the environment (salt, sand, moisture, chemicals, etc.) in which is used. Without taking wear or mechanical damage into account and in compliance with the conditions specified in the instructions for use this product may be used 15 years from the date of production and 10 years from the date of the first use.
However mechanical damage can occur during the first use, which can limit the lifetime of this products only to its first use.

beware of salt | beware of UV | beware of chemicals | washing | drying | read instructions

RELATED PRODUCTS

	BODY W0071	**BASIC** W0089SY
STANDARDS	EN 361	EN 361
WEIGHT	1 240 g [size XL/XXL]	885 g [size XL/XXL]

NOTES

info@singingrock.cz
www.singingrock.com