

# BODY II

## energy speed

Fully adjustable fall-arrest harness with various attachment points, speed buckles and comfortable padding. Suitable for working situations with maximum freedom of movement during work positioning.

### DESCRIPTION

Removable and washable shoulder and leg loops padding provides great comfort.

Integrated loops on the shoulder padding for hooks storage. Maximum load capacity 1.5 kg.

Webbing stitched in the buckles simplifies handling.

Front attachment point for fall arrest according to EN 361 marked with additional „A” marking.

Speed buckles enable fluent and fast adjustment to fit the user's body.

Two gear loops with max. load 15 kg.



Shoulder and leg loop padding with reflective straps provide higher visibility in dark conditions.

Rear attachment point according to EN 361 marked with „A” label.

Mesh net triangle for higher ventilation.

Waist belt allows horizontal or vertical movement.

Side attachment points for work positioning according to EN 358.

4 additional plastic hooks for light gear attachment.

### KEY FEATURES

- removable and washable shoulder and leg loops padding
- stitched waist belt padding allows horizontal or vertical movement of the padding

### STANDARDS

CE 1019

EN 361:02

EN 358:99

### FEATURES



XL/XXL  
2 450 g / 78.8 oz



unique  
number




3  
YEARS  
warranty

### MATERIALS



- 40% PES
- 27% EVA foam
- 10% PAD
- 9% steel
- 6% light alloy
- 5% PE
- 3% synthetic rubber

### TECHNICAL DATA



	S/M/L	XL/XXL	XXXL
A [cm]	75-125	85-135	100-160
A [in]	29.5-49	33-53	39-63
B [cm]	55-70	65-90	65-105
B [in]	21.6-27.5	25.6-35.5	25.6-41
C [cm]	150-185	180-210	180-210
C [ft]	4.9-6	5.9-6.8	5.9-6.8
m [g]	2 250	2 450	2 600

